



## Charger 24V/DC SLA (C-AH-00604)

### Specifications

|                         |                                   |
|-------------------------|-----------------------------------|
| Input voltage           | 100-240 VAC 50-60Hz               |
| Input current           | 700-500mA                         |
| Output voltage          | 24 V/DC                           |
| Output current          | 400mA                             |
| IP class charger        | IP40                              |
| Certification           | UL2601-1 IEC60601-1 IEC60335-2-29 |
| Operational temperature | 0°C to +40°C                      |
| Storage temperature     | -40°C to +70°C                    |
| Case colour             | Black                             |
| Dimensions LxWxH        | 109x69x39mm                       |

### Order Information

|                 |  |
|-----------------|--|
| Article number  | C-AH-00601 for EU<br>C-AH-00602 for GB<br>C-AH-00603 for AUS<br>C-AH-00604 for USA |
| Replacement for | NDA8200/NDA1200/HMX987   |
| Packaging       | Individually packed, 50pcs per box   |
| M.O.Q.          | 1 piece  |
| Delivery Time   | 2-5 working days   |



### Features

- + Suitable for AH-001X0 / NDA0100 / HMX991/ NDA0200
- + Charger specifically designed for medical equipment
- + Delivered with power cord suited for UK, EU, USA or AUS
- + When the battery pack is charged, the charger will continue as trickle charger